NSN 5905-01-376-2915

Noninductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-376-2915

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-100.0/+100.0

Electrical Resistance:

11.000 ohms

Resistance Tolerance In Percent:

-1.000/+1.000

Ambient Tempurature In Deg Celsius At Full Rated Power:

25.0

Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

275.0

Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+275.0

Inclosure Method:

Encased

Terminal Type:

Threaded stud

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

0.010

Terminal Length:

Between 1.188 inches and 1.312 inches

Body Length:

Between 4.406 inches and 4.594 inches

Body Width:

Between 2.094 inches and 2.156 inches

Body Height:

Between 2.157 inches and 2.219 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 2.990 inches and 3.010 inches

Power Dissipation Rating In Watts:

75.000 free air

Mounting Hole Size:

Between 0.178 inches and 0.198 inches

Style Designator:

Axial terminal (s)

Test Data Document:

81349-mil-r-18546 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-r-18546/2 government specification

Shelf Life:

N/a

NSN 5905-01-376-2915

Noninductive Wire Wound Fixed Resistor - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A001a0