## NSN 5905-01-376-7562

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-376-7562 **Section Quantity: Body Style:** Rectangular **Reliability Indicator:** Not established **Body Length:** 0.067 inches **Body Width:** 0.150 inches **Body Height:** 0.176 inches **Shaft Bearing Type:** Bearing **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 360.0 **Maximum Starting Torque:** 4.86 inch-ounces **Maximum Running Torque:** 4.86 inch-ounces **Terminal Location:** Lower adjacent side two rows **Mounting Method:** Tab **Features Provided:** Humidity proof **Electrical Resistance Per Section:** 500.0 ohms single section **Rotary Actuator Travel In Angular Deg:** 360.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 100.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -250.0/+250.0 single section **Power Dissipation Rating Per Section In Watts:** 0.1 free air single section **Resistance Tolerance Per Section In Percent:** -30.0/+30.0 single section

**Actuator Travel Control Feature:** Clutch

## NSN 5905-01-376-7562

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature	In Deg	Celsius Po	er Section	At Full Rated	d Power:
---------------------	--------	------------	------------	---------------	----------

70.0 single section

**Standard Taper Curve Per Section:** 

A single section

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A002a0