NSN 5905-01-377-2638

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-377-2638

Electrical Resistance: 220.000 ohms Resistance Tolerance In Percent: -5.000/+5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Quantity: 16 Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: Between 0.120 inches and 0.145 inches Body Length: Between 0.840 inches and 0.860 inches Body Width: Between 0.300 inches and 0.320 inches Body Height: Between 0.115 inches and 0.125 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 1.000 total network	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Electrical Resistance: 220.000 ohms Resistance Tolerance In Percent: -5.000/+5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Quantity: 16 Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: Between 0.120 inches and 0.145 inches Body Length: Between 0.840 inches and 0.860 inches Body Width: Between 0.300 inches and 0.320 inches Body Height: Between 0.115 inches and 0.125 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts:	
220.000 ohms Resistance Tolerance In Percent: -5.000/+5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Quantity: 16 Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: Between 0.120 inches and 0.145 inches Body Length: Between 0.840 inches and 0.860 inches Body Width: Between 0.300 inches and 0.320 inches Body Height: Between 0.115 inches and 0.125 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts:	
Resistance Tolerance In Percent: -5.000/+5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Quantity: 16 Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: Between 0.120 inches and 0.145 inches Body Length: Between 0.840 inches and 0.860 inches Body Width: Between 0.300 inches and 0.320 inches Body Height: Between 0.115 inches and 0.125 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts:	
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Quantity: 16 Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: Between 0.120 inches and 0.145 inches Body Length: Between 0.840 inches and 0.860 inches Body Width: Between 0.300 inches and 0.320 inches Body Height: Between 0.115 inches and 0.125 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts:	
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Quantity: 16 Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: Between 0.120 inches and 0.145 inches Body Length: Between 0.840 inches and 0.860 inches Body Width: Between 0.300 inches and 0.320 inches Body Height: Between 0.115 inches and 0.125 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Quantity: 16 Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: Between 0.120 inches and 0.145 inches Body Length: Between 0.840 inches and 0.860 inches Body Width: Between 0.300 inches and 0.320 inches Body Height: Between 0.115 inches and 0.125 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Quantity: 16 Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: Between 0.120 inches and 0.145 inches Body Length: Between 0.840 inches and 0.860 inches Body Width: Between 0.300 inches and 0.320 inches Body Height: Between 0.115 inches and 0.125 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts:	•
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Quantity: 16 Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: Between 0.120 inches and 0.145 inches Body Length: Between 0.840 inches and 0.860 inches Body Width: Between 0.300 inches and 0.320 inches Body Height: Between 0.115 inches and 0.125 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts:	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Quantity: 16 Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: Between 0.120 inches and 0.145 inches Body Length: Between 0.840 inches and 0.860 inches Body Width: Between 0.300 inches and 0.320 inches Body Height: Between 0.115 inches and 0.125 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts:	-
-55.0/+150.0 Inclosure Method: Encapsulated Terminal Quantity: 16 Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: Between 0.120 inches and 0.145 inches Body Length: Between 0.840 inches and 0.860 inches Body Width: Between 0.300 inches and 0.320 inches Body Height: Between 0.115 inches and 0.125 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts:	
Inclosure Method: Encapsulated Terminal Quantity: 16 Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: Between 0.120 inches and 0.145 inches Body Length: Between 0.840 inches and 0.860 inches Body Width: Between 0.300 inches and 0.320 inches Body Height: Between 0.115 inches and 0.125 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts:	
Encapsulated Terminal Quantity: 16 Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: Between 0.120 inches and 0.145 inches Body Length: Between 0.840 inches and 0.860 inches Body Width: Between 0.300 inches and 0.320 inches Body Height: Between 0.115 inches and 0.125 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts:	
Terminal Quantity: 16 Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: Between 0.120 inches and 0.145 inches Body Length: Between 0.840 inches and 0.860 inches Body Width: Between 0.300 inches and 0.320 inches Body Height: Between 0.115 inches and 0.125 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts:	
Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: Between 0.120 inches and 0.145 inches Body Length: Between 0.840 inches and 0.860 inches Body Width: Between 0.300 inches and 0.320 inches Body Height: Between 0.115 inches and 0.125 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts:	·
Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: Between 0.120 inches and 0.145 inches Body Length: Between 0.840 inches and 0.860 inches Body Width: Between 0.300 inches and 0.320 inches Body Height: Between 0.115 inches and 0.125 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts:	
Tab, solder lug Reliability Indicator: Not established Terminal Length: Between 0.120 inches and 0.145 inches Body Length: Between 0.840 inches and 0.860 inches Body Width: Between 0.300 inches and 0.320 inches Body Height: Between 0.115 inches and 0.125 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts:	
Reliability Indicator: Not established Terminal Length: Between 0.120 inches and 0.145 inches Body Length: Between 0.840 inches and 0.860 inches Body Width: Between 0.300 inches and 0.320 inches Body Height: Between 0.115 inches and 0.125 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts:	•
Not established Terminal Length: Between 0.120 inches and 0.145 inches Body Length: Between 0.840 inches and 0.860 inches Body Width: Between 0.300 inches and 0.320 inches Body Height: Between 0.115 inches and 0.125 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts:	-
Terminal Length: Between 0.120 inches and 0.145 inches Body Length: Between 0.840 inches and 0.860 inches Body Width: Between 0.300 inches and 0.320 inches Body Height: Between 0.115 inches and 0.125 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts:	-
Between 0.120 inches and 0.145 inches Body Length: Between 0.840 inches and 0.860 inches Body Width: Between 0.300 inches and 0.320 inches Body Height: Between 0.115 inches and 0.125 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts:	
Body Length: Between 0.840 inches and 0.860 inches Body Width: Between 0.300 inches and 0.320 inches Body Height: Between 0.115 inches and 0.125 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts:	
Between 0.840 inches and 0.860 inches Body Width: Between 0.300 inches and 0.320 inches Body Height: Between 0.115 inches and 0.125 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts:	
Body Width: Between 0.300 inches and 0.320 inches Body Height: Between 0.115 inches and 0.125 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts:	
Between 0.300 inches and 0.320 inches Body Height: Between 0.115 inches and 0.125 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts:	
Body Height: Between 0.115 inches and 0.125 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts:	•
Between 0.115 inches and 0.125 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts:	
Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts:	
Ladder network Power Dissipation Rating In Watts:	
Power Dissipation Rating In Watts:	
1.000 total notwork	
Terminal Width:	
Between 0.015 inches and 0.021 inches	••••••
Identical Value Resistor Quantity:	
15 each resistor	
Style Designator:	
Dual inline	
Shelf Life:	
N/a	
Unit Of Measure:	

--

NSN 5905-01-377-2638

Film Fixed Resistor Network - Page 2 of 2



Demilitarization:

No

Fiig:

A001a0