Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-378-8694

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-300.0/+300.0

Electrical Resistance:

2.050 kilohms

Resistance Tolerance In Percent:

-1.000/+1.000

Ambient Tempurature In Deg Celsius At Full Rated Power:

70.0

Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

125.0

Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+125.0

Inclosure Method:

Encapsulated

Terminal Quantity:

10

Terminal Type:

Pin

Reliability Indicator:

Not established

Terminal Length:

Between 0.125 inches and 0.150 inches

Body Length:

Between 0.968 inches and 0.998 inches

Body Width:

Between 0.050 inches and 0.103 inches

Body Height:

Between 0.332 inches and 0.352 inches

Schematic Diagram Designator:

Ladder network

Power Dissipation Rating In Watts:

1.800 total network

Identical Value Resistor Quantity:

9 each resistor

Style Designator:

Single inline

Test Data Document:

81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-r-83401/6 government specification

Shelf Life:

N/a

Film Fixed Resistor Network - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A001a0