Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-380-8326

## Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-50.0/+50.0

### **Electrical Resistance:**

3.300 kilohms

**Resistance Tolerance In Percent:** 

-5.000/+5.000

### Ambient Tempurature In Deg Celsius At Full Rated Power:

### 70.0

## Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

125.0

## Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+125.0

### **Inclosure Method:**

Encapsulated

### **Terminal Quantity:**

10

## Terminal Type:

Pin

## **Reliability Indicator:**

Not established

## Terminal Length:

Between 0.125 inches and 0.150 inches

## **Body Length:**

Between 0.968 inches and 0.998 inches

## **Body Width:**

Between 0.050 inches and 0.103 inches

## **Body Height:**

Between 0.177 inches and 0.197 inches

## Schematic Diagram Designator:

Ladder network

**Power Dissipation Rating In Watts:** 

0.540 total network

## **Identical Value Resistor Quantity:**

9 each resistor

#### Style Designator:

Single inline

## **Test Data Document:**

81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-r-83401/9 government specification

# Shelf Life:

N/a

Film Fixed Resistor Network - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A001a0