Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-380-9726

# Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-100.0/+100.0

#### **Electrical Resistance:**

20.000 kilohms

# **Resistance Tolerance In Percent:**

-2.000/+2.000

#### Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 70.0

# Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

125.0

# Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+125.0

#### **Inclosure Method:**

Encapsulated

#### **Terminal Quantity:**

**Terminal Type:** 

Pin

8

# **Reliability Indicator:**

Not established

# **Body Length:**

Between 0.768 inches and 0.798 inches

# **Body Width:**

Between 0.050 inches and 0.103 inches

#### **Body Height:**

Between 0.177 inches and 0.197 inches

# Schematic Diagram Designator:

Ladder network

**Power Dissipation Rating In Watts:** 

0.840 total network

**Identical Value Resistor Quantity:** 

7 each resistor

#### Style Designator:

Single inline

# **Test Data Document:**

81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Specification Data:**

81349-mil-r-83401/8 government specification

# Shelf Life:

N/a

# NSN 5905-01-380-9726

Film Fixed Resistor Network - Page 2 of 2

Demilitarization:

No

Fiig:

A001a0

