NSN 5905-01-381-0426

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-381-0426

Section Quantity:
2
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
Between 1.032 inches and 1.156 inches
Shaft Diameter:
0.0250 inches
Shaft Length:
0.875 inches
Mounting Bushing Length:
Between 0.360 inches and 0.432 inches
Body Length:
1.359 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
150.0 ohms c and better industrial clears
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 all sections
Power Dissipation Rating Per Section In Watts:
1.38 7th secondary pattern
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 all sections
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

NSN 5905-01-381-0426

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Fiig: A002a0