NSN 5905-01-382-6340

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-382-6340 **Section Quantity: Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 0.9683 inches and 0.9688 inches Pilot Length: Between 0.0570 inches and 0.0620 inches **Undercut Diameter:** 0.975 inches **Undercut Width:** 0.0570 inches **Body Diameter:** 1.125 inches **Shaft Diameter:** Between 0.1245 inches and 0.1250 inches **Mounting Lip Diameter:** Between 1.0520 inches and 1.0670 inches **Mounting Lip Depth:** Between 0.0570 inches and 0.0670 inches **Shaft Style:** Round **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Clamp ring **Features Provided:** Humidity proof **Electrical Resistance Per Section:** 50.0 kilohms single section **Terminal Type And Quantity:** 3 turret

Shelf Life: N/a **Unit Of Measure:**

NSN 5905-01-382-6340

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



_						
11	em)	 tor	172	+ 1	nn	

No

Fiig:

A002a0