Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-383-9089

# Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-300.0/+300.0

#### **Electrical Resistance:**

4.700 kilohms

**Resistance Tolerance In Percent:** 

-0.500/+0.500

#### Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 70.0

# Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

125.0

# Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+125.0

#### **Inclosure Method:**

Encapsulated

#### **Terminal Quantity:**

16

# Terminal Type:

Tab, solder lug

#### Reliability Indicator:

Not established

# Terminal Length:

Between 0.145 inches and 0.215 inches

# **Body Length:**

Between 0.784 inches and 0.876 inches

#### **Body Width:**

Between 0.240 inches and 0.305 inches

#### **Body Height:**

0.180 inches

Schematic Diagram Designator:

Ladder network

#### **Power Dissipation Rating In Watts:**

1.500 total network

#### **Identical Value Resistor Quantity:**

15 each resistor

# Style Designator:

Dual inline

# **Test Data Document:**

81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Specification Data:**

81349-mil-r-83401/2 government specification

# Shelf Life:

N/a

Film Fixed Resistor Network - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A001a0