Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-385-4611

## Section Quantity:

1

**Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Terminal Length:** Between 0.531 inches and 0.563 inches **Body Diameter:** Between 0.484 inches and 0.516 inches Shaft Diameter: Between 0.124 inches and 0.126 inches Shaft Length: Between 0.859 inches and 0.891 inches Mounting Bushing Length: Between 0.359 inches and 0.391 inches **Body Length:** 0.594 inches Shaft Style: Round, slotted Shaft Bearing Type: Sleeve Actuator Type: Single shaft Effective Electrical Rotation In Deg Angular Rotation: 270.0 Maximum Starting Torque: 3.00 inch-ounces Maximum Running Torque: 3.00 inch-ounces Maximum Stop Torque: 64.00 inch-ounces

#### **Nonturn Device Location:**

At 3 oclock and at 9 oclock

**Nonturn Device Radius:** 

Between 0.240 inches and 0.250 inches

#### Mechanical Backlash In Deg Angular Rotation:

3.0

### Center To Center Distance Between Terminals:

Between 0.195 inches and 0.205 inches

#### Screw Thread Diameter:

Between 0.240 inches and 0.250 inches

# NSN 5905-01-385-4611

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



**Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear end **Mounting Method:** Standard bushing and terminal **Center To Center Distance Between Terminal Rows:** Between 0.095 inches and 0.105 inches **Features Provided:** Humidity proof **Electrical Resistance Per Section:** 25.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** Between 290.0 and 300.0 Center To Center Distance Between Center Terminal And Outside Terminal: Between 0.095 inches and 0.105 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 120.0 single section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:** -20.0/+20.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A002a0