

View Online at <https://aerobasegroup.com/nsn/5905-01-386-0078>

**Section Quantity:**

1

**Body Style:**

Rectangular

**Reliability Indicator:**

Not established

**Terminal Length:**

0.004 inches

**Body Length:**

Between 0.094 inches and 0.118 inches

**Body Width:**

Between 0.185 inches and 0.209 inches

**Body Height:**

Between 0.165 inches and 0.189 inches

**Actuator Type:**

Flush drive with slot-hole

**Effective Electrical Rotation In Deg Angular Rotation:**

200.0

**Maximum Starting Torque:**

2.10 inch-ounces

**Maximum Running Torque:**

2.10 inch-ounces

**Maximum Stop Torque:**

4.10 inch-ounces

**Center To Center Distance Between Terminals:**

Between 0.078 inches and 0.102 inches

**Terminal Location:**

Lower adjacent side two rows

**Mounting Method:**

Terminal

**Center To Center Distance Between Terminal Rows:**

0.160 inches

**Electrical Resistance Per Section:**

20.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

Between 250.0 and 270.0

**Center To Center Distance Between Center Terminal And Outside Terminal:**

Between 0.033 inches and 0.057 inches

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

125.0 single section

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-100.0/+100.0 single section

**Power Dissipation Rating Per Section In Watts:**

0.25 free air single section

**Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 single section

**Actuator Travel Control Feature:**

Stops

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

3 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0