## NSN 5905-01-386-8072

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-386-8072 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.525 inches **Shaft Diameter:** Between 0.124 inches and 0.126 inches **Shaft Length:** 0.124 inches **Mounting Bushing Length:** Between 0.453 inches and 0.547 inches **Body Length:** Between 0.625 inches and 0.687 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 295.0 and 305.0 **Maximum Starting Torque:** 3.00 inch-ounces **Maximum Running Torque:** 3.00 inch-ounces **Maximum Stop Torque:** 80.00 inch-ounces **Nonturn Device Location:** At 3 oclock **Nonturn Device Radius:** 0.250 inches **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0

Terminal Location:
Rear end

## NSN 5905-01-386-8072

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Mounting Method:
Locking bushing
Features Provided:
Humidity proof
Electrical Resistance Per Section:
350.0 ohms single section
Rotary Actuator Travel In Angular Deg:
Between 295.0 and 305.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
340.0 single section
Power Dissipation Rating Per Section In Watts:
5.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-mil-r-22 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 tab, solder lug
Specification Data:
81349-mil-r-22/15 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0