NSN 5905-01-387-9984

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-387-9984 **Section Quantity:** 2 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.75000 inches Pilot Length: 0.06200 inches **Overall Length:** 1.310 inches **Undercut Diameter:** 0.781 inches **Undercut Width:** 0.05700 inches **Body Diameter:** 0.906 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.500 inches **Body Length:** 0.810 inches **Overall Diameter:** 1.312 inches **Mounting Lip Diameter:** 0.87500 inches **Mounting Lip Depth:** 0.06200 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 320.0 **Maximum Starting Torque:**

0.50 inch-ounces

Maximum Running Torque:

0.40 inch-ounces

NSN 5905-01-387-9984

A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Shaft End Play:
0.00500 inches
Shaft Runout:
0.001 inches
Lateral Runout:
0.001 inches
Pilot Diameter Runout:
0.00100 inches
Shaft Radial Play:
0.001 inches
Mechanical Backlash In Deg Angular Rotation:
0.25
Fragility Factor:
Moderately delicate
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
1.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Resistance Tempurature Characteristic Range Per Section In Percent:
-5.0/+5.0 -65 degrees celsius 2nd section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Test Data Document:
81349-mil-r-39023 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 turret
Specification Data:
81349-mil-r0-39023/1 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiia: