NSN 5905-01-389-7102

No Fiig: A001a0

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-389-7102

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: 10.0/+10.0 Electrical Resistance: 3.120 kilohms Resistance Tolerance In Percent: 0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Inclosure Method: Encapsulated
Electrical Resistance: 3.120 kilohms Resistance Tolerance In Percent: 0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Inclosure Method: Encapsulated
Resistance Tolerance In Percent: 0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Inclosure Method: Encapsulated
Resistance Tolerance In Percent: 0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Inclosure Method: Encapsulated
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 nclosure Method: Encapsulated
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Inclosure Method: Encapsulated
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 nclosure Method: Encapsulated
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 nclosure Method: Encapsulated
I45.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 nclosure Method: Encapsulated
Fempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 nclosure Method: Encapsulated
65.0/+145.0 nclosure Method: Encapsulated
nclosure Method: Encapsulated
Encapsulated
Ferminal Type:
Wire lead
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.010
Terminal Length:
1.500 inches
Body Diameter:
Between 0.235 inches and 0.265 inches
Body Length:
Between 0.312 inches and 0.364 inches
Power Dissipation Rating In Watts:
0.125 free air
Style Designator:
Axial terminal each end
Test Data Document:
31349-mil-r-39005 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
31349-mil-r-39005/5 government specification
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization: