NSN 5905-01-390-0126

Precision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-390-0126 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.500 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.625 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Maximum Starting Torque:** 0.80 inch-ounces **Maximum Running Torque:** 0.80 inch-ounces **Shaft End Play:** 0.010 inches **Shaft Runout:** 0.003 inches **Lateral Runout:** 0.005 inches **Pilot Diameter Runout:** 0.004 inches **Shaft Radial Play:** 0.003 inches **Mechanical Backlash In Deg Angular Rotation:** 1.0 **Terminal Location:** Upper adjacent side single row **Mounting Method:** Shaft

Electrical Resistance Per Section:

100.0 kilohms single section

NSN 5905-01-390-0126

Precision Nonwire Wound Variable Resistor - Page 2 of 2



Function Conformity Tolerance Per Section:

-0.25/+0.25 single section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-150.0/+100.0 single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

Function Conformity Per Section:

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Function Characteristic Per Section:

Single section linear

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

Terminal Type And Quantity:

2 turret

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0