Precision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-392-2223

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

0.440 inches

Shaft Diameter:

0.125 inches

Shaft Length:

1.590 inches

Mounting Bushing Length:

0.186 inches

Body Length:

0.414 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Maximum Starting Torque:

0.50 inch-ounces

Maximum Running Torque:

0.50 inch-ounces

Shaft End Play:

0.005 inches

Shaft Runout:

0.002 inches

Lateral Runout:

0.001 inches

Pilot Diameter Runout:

0.001 inches

Shaft Radial Play:

0.001 inches

Mechanical Backlash In Deg Angular Rotation:

10.0

Terminal Location:

Upper adjacent side single row

Electrical Resistance Per Section:

3.0 kilohms single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

NSN 5905-01-392-2223

Precision Nonwire Wound Variable Resistor - Page 2 of 2



Function Conformity Per Section: Single section absolute linearity **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Function Characteristic Per Section:** Single section linear Terminal Type And Quantity: 3 wire lead Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A002a0