Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-396-7902

# Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-300.0/+300.0 first temp coefficient

### **Electrical Resistance:**

2.050 kilohms

## **Resistance Tolerance In Percent:**

-2.000/+2.000

## Ambient Tempurature In Deg Celsius At Full Rated Power:

### 70.0

## Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

125.0

## Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+125.0 temp range of first temp coefficient

### **Inclosure Method:**

Encapsulated

### **Terminal Quantity:**

**Terminal Type:** 

Pin

8

## **Reliability Indicator:**

Not established

# **Body Length:**

Between 0.768 inches and 0.798 inches

## **Body Width:**

Between 0.050 inches and 0.103 inches

### **Body Height:**

Between 0.332 inches and 0.350 inches

## Schematic Diagram Designator:

Ladder network

**Power Dissipation Rating In Watts:** 

1.400 total network

**Identical Value Resistor Quantity:** 

7 each resistor

### Style Designator:

Single inline

## **Test Data Document:**

81349-mil-r-83401/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-r-83401/5 government specification

Shelf Life:

N/a

Film Fixed Resistor Network - Page 2 of 2

Demilitarization:

No

Fiig:

A001a0

