Nonprecision Wire Wound Variable Resistor - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5905-01-396-8601

Section Quantity:

1

- **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 2.410 inches Shaft Diameter: Between 0.249 inches and 0.251 inches Shaft Length: 2.500 inches **Mounting Bushing Length:** Between 0.328 inches and 0.422 inches **Body Length:** 1.440 inches Shaft Style: Round, slotted Actuator Type: Single shaft **Screw Thread Diameter:** 0.375 inches
- Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

5.0 kilohms single section

Power Dissipation Rating Per Section In Watts:

50.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A002a0