## NSN 5905-01-396-8806

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-396-8806

Electrical Resistance: 78.700 kilohms  Resistance Tolerance In Percent: -1.000/+1.000  Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0  Inclosure Method: Encapsulated Reliability Indicator: Not established  Test Data Document: 81349-mil-r-10509 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	on
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Inclosure Method: Encapsulated Reliability Indicator: Not established Test Data Document: 81349-mil-r-10509 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	on
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Inclosure Method: Encapsulated Reliability Indicator: Not established Test Data Document: 81349-mil-r-10509 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification (ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	on
Ambient Tempurature In Deg Celsius At Full Rated Power:  125.0  Inclosure Method:  Encapsulated  Reliability Indicator:  Not established  Test Data Document:  81349-mil-r-10509 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	on
Ambient Tempurature In Deg Celsius At Full Rated Power:  125.0  Inclosure Method:  Encapsulated  Reliability Indicator:  Not established  Test Data Document:  81349-mil-r-10509 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	on
Inclosure Method: Encapsulated Reliability Indicator: Not established Test Data Document: 81349-mil-r-10509 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification (format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	on
Inclosure Method: Encapsulated Reliability Indicator: Not established Test Data Document: 81349-mil-r-10509 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	on
Encapsulated  Reliability Indicator:  Not established  Test Data Document:  81349-mil-r-10509 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	on
Reliability Indicator:  Not established  Test Data Document:  81349-mil-r-10509 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	on
Not established  Test Data Document:  81349-mil-r-10509 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	on
Test Data Document: 81349-mil-r-10509 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	on
81349-mil-r-10509 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specificati format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	on
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	on
	٠.,
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Shelf Life:	
N/a	
Unit Of Measure:	
<del></del>	
Demilitarization:	
No	
Fiig:	
A001a0	