## NSN 5905-01-398-2220

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-398-2220 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established Flat Height: Between 0.211 inches and 0.221 inches **Body Diameter:** 1.094 inches **Shaft Diameter:** Between 0.248 inches and 0.251 inches **Shaft Length:** 0.875 inches **Mounting Bushing Length:** Between 0.344 inches and 0.390 inches **Body Length:** Between 0.468 inches and 0.656 inches **Shaft Style:** Round, flatted **Actuator Type:** Single shaft **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 500.0 ohms single section **Power Dissipation Rating Per Section In Watts:** 2.0 free air single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Standard Taper Curve Per Section:** 

A single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

## NSN 5905-01-398-2220

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Fiig:

A002a0