NSN 5905-01-406-5654

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-406-5654

Continu Overstitus
Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Established Reliability Feilure Rete Level In Research
Reliability Failure Rate Level In Percent: 0.100
Terminal Length: 0.300 inches
Shaft Diameter:
0.075 inches
Shaft Length: 0.080 inches
Body Length: 0.420 inches
Body Width:
0.170 inches
Body Height:
0.375 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Center To Center Distance Between Terminals:
0.200 inches
Terminal Location:
Rear end
Mounting Method:
Terminal
Electrical Resistance Per Section:
50.000 kilohms single section
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0/+100.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Terminal Type And Quantity:

3 pin

NSN 5905-01-406-5654

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Specification Data:
81349-mil-r-39035/2 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0