NSN 5905-01-406-7213

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-406-7213 **Section Quantity: Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Established **Reliability Failure Rate Level In Percent:** 0.010 **Mounting Hole Diameter:** 0.093 inches **Body Length:** Between 1.240 inches and 1.260 inches **Body Width:** Between 0.180 inches and 0.200 inches **Body Height:** Between 0.300 inches and 0.330 inches **Actuator Type:** Flush drive with slot-hole **Lateral Distance Between Mounting Hole Centers:** 1.000 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Electrical Resistance Per Section:** 50.000 kilohms single section **Power Dissipation Rating Per Section In Watts:** 0.7 free air single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Special Features:** Wattage is 0.75 **Terminal Type And Quantity:** 3 wire lead Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5905-01-406-7213

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Fiig:

A002a0