NSN 5905-01-406-9856

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-406-9856 **Section Quantity:** 2 **Body Style:** Rectangular bushing mounted **Reliability Indicator:** Not established **Shaft Diameter:** 0.249 inches **Shaft Length:** 0.375 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Lower adjacent side two rows **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 10.0 kilohms all sections Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 all sections **Power Dissipation Rating Per Section In Watts:** 1.8 free air all sections **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 all sections Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 all sections **Terminal Type And Quantity:** 6 tab, solder lug Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5905-01-406-9856

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Fiig:

A002a0