Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-407-6356

| Section Quantity:   |
|---|
| 1   |
| Body Style:   |
| Rectangular   |
| Reliability Indicator:  |
| Not established   |
| Shaft Diameter:   |
| 0.070 inches  |
| Body Length:  |
| Between 0.250 inches and 0.290 inches                                       |
| Body Width:   |
| Between 0.155 inches and 0.185 inches                                       |
| Body Height:  |
| Between 0.230 inches and 0.270 inches                                       |
| Shaft Style:  |
| Round, slotted  |
| Actuator Type:  |
| Single shaft  |
| Center To Center Distance Between Terminals:                                |
| 0.100 inches  |
| Terminal Location:  |
| Rear end  |
| Mounting Method:  |
| Terminal  |
| Electrical Resistance Per Section:  |
| 500000.000 ohms single section  |
| Center To Center Distance Between Center Terminal And Outside Terminal:     |
| 0.100 inches  |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 125.0 single section  |
| Power Dissipation Rating Per Section In Watts:                              |
| 0.25 free air single section  |
| Resistance Tolerance Per Section In Percent:                                |
| -10.0/+10.0 single section  |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:         |
| 70.0 single section   |
| Terminal Type And Quantity:   |
| 3 pin   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |

---

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A002a0