NSN 5905-01-412-0468

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-412-0468

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: |
|--|
| -300.0/+300.0 |
| Electrical Resistance: |
| 200.000 ohms |
| Resistance Tolerance In Percent: |
| -1.000/+1.000 |
| Ambient Tempurature In Deg Celsius At Full Rated Power: |
| 70.0 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| 125.0 |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: |
| -55.0/+125.0 |
| Inclosure Method: |
| Encapsulated |
| Terminal Quantity: |
| 8 |
| Terminal Type: |
| Pin |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| Between 0.125 inches and 0.150 inches |
| Body Length: |
| Between 0.768 inches and 0.798 inches |
| Body Width: |
| Between 0.050 inches and 0.103 inches |
| Body Height: |
| Between 0.332 inches and 0.350 inches |
| Schematic Diagram Designator: |
| Isolated array |
| Power Dissipation Rating In Watts: |
| 0.800 total network |
| Identical Value Resistor Quantity: |
| 4 each resistor |
| Style Designator: |
| Single inline |
| Test Data Document: |
| 81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Specification Data: |
| 81349-mil-r-83401/5 government specification |

N/a

Shelf Life:

NSN 5905-01-412-0468

Film Fixed Resistor Network - Page 2 of 2



| | | | ure: | |
|--|--|--|------|--|
| | | | | |
| | | | | |

--

Demilitarization:

No

Fiig:

A001a0