## NSN 5905-01-417-1896

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-417-1896 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.375 inches **Shaft Diameter:** Between 0.124 inches and 0.126 inches **Shaft Length:** 0.438 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** Between 0.407 inches and 0.469 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear end **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 50.0 kilohms single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Terminal Type And Quantity:** Wire loop Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5905-01-417-1896

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A002a0