Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-418-4893

Section Quantity:

1

Body Style:

Rectangular w/pointer adjustment

Reliability Indicator:

Not established

Terminal Length:

12.7 millimeters

Body Length:

Between 6.9 millimeters and 7.6 millimeters

Body Width:

Between 11.1 millimeters and 11.8 millimeters

Body Height:

Between 12.9 millimeters and 13.7 millimeters

Actuator Type:

Flush drive with slot-hole

Center To Center Distance Between Terminals:

2.5 millimeters

Terminal Location:

Lower adjacent side two rows

Mounting Method:

Terminal

Center To Center Distance Between Terminal Rows:

2.5 millimeters

Electrical Resistance Per Section:

1000.0 ohms single section

Center To Center Distance Between Center Terminal And Outside Terminal:

2.5 millimeters

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A002a0