NSN 5905-01-418-4894

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-418-4894 **Section Quantity: Body Style:** Rectangular w/pointer adjustment **Reliability Indicator:** Not established **Terminal Length:** 12.7 millimeters **Body Length:** Between 6.9 millimeters and 7.6 millimeters **Body Width:** Between 11.1 millimeters and 11.8 millimeters **Body Height:** Between 12.9 millimeters and 13.7 millimeters **Actuator Type:** Flush drive with slot-hole **Center To Center Distance Between Terminals:** 2.5 millimeters **Terminal Location:** Lower adjacent side two rows **Mounting Method: Terminal Center To Center Distance Between Terminal Rows:** 2.5 millimeters **Electrical Resistance Per Section:** 20000.0 ohms single section **Center To Center Distance Between Center Terminal And Outside Terminal:** 2.5 millimeters Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a

--

Unit Of Measure:

NSN 5905-01-418-4894

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



em			

No

Fiig:

A002a0