NSN 5905-01-420-8605

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-420-8605

Section Overtity
Section Quantity:
Body Style:
Rectangular w/mounting holes
Reliability Indicator:
Not established
Mounting Hole Diameter:
2.4 millimeters
Shaft Diameter:
Between 1.7 millimeters and 2.3 millimeters
Shaft Length:
Between 0.6 millimeters and 1.1 millimeters
Body Length:
12.7 millimeters
Body Width:
4.7 millimeters
Body Height:
12.7 millimeters
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Lateral Distance Between Mounting Hole Centers:
Between 13.0 millimeters and 13.4 millimeters
Mounting Facility Quantity:
2
Terminal Location:
Rear end
Mounting Method:
Unthreaded hole
Electrical Resistance Per Section:
1000.0 ohms single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Terminal Type And Quantity:
Outing lead

3 wire lead

NSN 5905-01-420-8605

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0