NSN 5905-01-422-6872

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-422-6872 **Section Quantity: Body Style:** Cylindrical bushing mounted **Terminal Length:** 0.234 inches **Body Diameter:** 0.500 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** Between 0.469 inches and 0.593 inches **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 295.0 **Nonturn Device Location:** At 10 oclock **Nonturn Device Radius:** Between 0.240 inches and 0.250 inches **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear end **Mounting Method:** Standard bushing **Features Provided:** Humidity proof **Electrical Resistance Per Section:** 1.0 kilohms single section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Standard Taper Curve Per Section:** A single section **Special Features:**

3 inch shaft

NSN 5905-01-422-6872

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0