NSN 5905-01-424-0798

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-424-0798

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
22.2 millimeters
Shaft Diameter:
8.3 millimeters
Shaft Length:
20.6 millimeters
Mounting Bushing Length:
7.9 millimeters
Body Length:
19.1 millimeters
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Pilot Diameter Runout:
0.1 millimeters
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Upper adjacent side single row
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
1000.0 ohms single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0/+100.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Precious Material And Location:

Terminal surfaces gold

NSN 5905-01-424-0798

Precision Wire Wound Variable Resistor - Page 2 of 2



Precious Material:
Gold
Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0