## NSN 5905-01-424-8454

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-424-8454 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** Between 0.480 inches and 0.520 inches **Mounting Bushing Length:** Between 0.134 inches and 0.266 inches **Body Length:** Between 0.469 inches and 0.593 inches **Actuator Type:** Flush drive with slot-hole **Center To Center Distance Between Terminals:** Between 0.195 inches and 0.205 inches **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear end **Mounting Method:** Locking bushing **Electrical Resistance Per Section:** 10.000 kilohms single section **Center To Center Distance Between Center Terminal And Outside Terminal:** Between 0.195 inches and 0.205 inches **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:** -10.000/+10.000 single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5905-01-424-8454

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Fiig:

A002a0