Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-424-8801

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

#### **Body Diameter:**

0.750 inches

#### Shaft Diameter:

0.125 inches

#### Shaft Length:

0.875 inches

#### Mounting Bushing Length:

0.250 inches

#### Body Length:

# 0.500 inches

Shaft Style:

Round

## Actuator Type:

Single shaft

# Nonturn Device Location:

At 9 oclock

# Nonturn Device Radius:

0.375 inches

# Screw Thread Diameter:

0.250 inches

# Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

#### **Terminal Location:**

Radially positioned over less than half the circumference

#### **Mounting Method:**

Standard bushing

#### **Electrical Resistance Per Section:**

10.0 kilohms single section

# Power Dissipation Rating Per Section In Watts:

1.0 free air single section

## **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

## Terminal Type And Quantity:

3 tab, solder lug

# NSN 5905-01-424-8801

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0