## NSN 5905-01-438-1329

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-438-1329 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Terminal Length:** 0.344 inches **Body Diameter:** 0.781 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.885 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 1.015 inches **Undercut Diameter:** 0.125 inches **Shaft Style:** Round, stepped **Actuator Type:** Dual concentric **Effective Electrical Rotation In Deg Angular Rotation:** 260.0 **Maximum Starting Torque:** 4.00 inch-ounces **Maximum Running Torque:** 2.00 inch-ounces **Maximum Stop Torque:** 32.00 inch-ounces **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.437 inches **Center To Center Distance Between Terminals:** 0.242 inches **End Application:** Hu-25 coast guard aircraft

**Undercut Length:** 

0.470 inches

## NSN 5905-01-438-1329

A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Facility Quantity:
1
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Center To Center Distance Between Terminal Rows:
0.480 inches
Electrical Resistance Per Section:
5.0 kilohms all sections
Rotary Actuator Travel In Angular Deg:
260.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.470 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 all sections
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-250.0 to 250.0 all sections
Power Dissipation Rating Per Section In Watts:
0.5 free air single section and 2.0 free air single section
Resistance Tolerance Per Section In Percent:
-20.0 to 20.0 4th section
Actuator Travel Control Feature:
Spring
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 all sections
Special Features:
Item consists of two resistors p/n c2-551 nsn 5905-00-233-3902 and p/n 539038-2 nsn 5905-00-164-1223 agavghu-25 coast guard aircraft
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig: