## NSN 5905-01-439-5749

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-439-5749

4.490 kilohms Resistance Tolerance in Percent: 1.000/4.1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Mil-std-1276 Wire Lead Type Designator: C Reflability Indicator: Established Reliability Indicator: Established Reliability Failure Rate Level in Percent: 0.001 Terminal Length: Between 0.984 inches and 1.516 inches Body Diameter: Between 0.080 inches and 0.080 inches Body Length: 0.150 inches Power Dissipation Rating in Watts: 0.050 free air 1845-mil-765182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 181349-mil-7651827 government specification Shelf Life: No Unit of Measure:	Electrical Resistance:
Resistance Tolerance in Percent: -1.0004-1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 175.0 Inclosure Method: Encapsulated Terminal Type: Wire laad Mill-std-1276 Wire Lead Type Designator: C Reliability Indicator: Established Reliability Failure Rate Level in Percent: 0.001 Terminal Longth: Between 0.984 inches and 1.516 inches Body Diameter: Between 0.985 inches and 0.080 inches Body Length: 0.155 inches Power Dissipation Rating in Watts: 0.056 free air Test Data Document: 81349-mill-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, inclustry directories, and similiar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mill-65182/7 government specification No Pilg: No Demilitarization: No Filig:	
Anbient Tempurature In Deg Celsius At Full Rated Power: 125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Mil-std-1276 Wire Lead Type Designator: C Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: Between 0.950 inches and 0.880 inches Body Diameter: Between 0.950 inches and 0.080 inches Body Length: 0.150 inches Power Dissipation Rating In Watts: 0.050 free air Test Data Document: Briad-mil-s5182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: Briad-mil-s5182/7 government specification Shelf Life: Na Unit Of Measure:	
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Milli-std-1276 Wire Lead Type Designator: C Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: Between 0.984 inches and 1.516 inches Beddy Length: 0.150 inches Power Dissipation Rating In Watts: 0.050 free air Test Data Document: 81349-mill-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mill-551827 government specification Sheff Life: N/a Unit Of Measure: Demilitarization: No Filg:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Milliestd-1276 Wire Lead Type Designator: C Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: Between 0.984 inches and 1.516 inches Body Diameter: Between 0.980 inches and 0.080 inches Body Length: 0.150 inches Power Dissipation Rating In Watts: 0.050 free air Test Data Document: B1439-mili-755182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: B1439-mili-755182/7 government specification Sheff Life: N/a Unit Of Measure:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Mil-std-1276 Wire Lead Type Designator: C Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: Between 0.984 inches and 1.516 inches Body Diameter: Between 0.984 inches and 0.080 inches Body Length: 0.150 inches Power Dissipation Rating in Watts: 0.050 free air Test Data Document: 81349-mil-s5182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mil-s51827 government specification Shelf Life: Na Unit Of Measure:	
Inclosure Method: Encapsulated Terminal Type: Wire lead Mil-std-1276 Wire Lead Type Designator: C Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: Between 0.984 inches and 1.516 inches Body Diameter: Between 0.984 inches and 0.080 inches Body Diameter: Between 0.050 inches and 0.080 inches Body Length: 0.150 inches Power Dissipation Rating In Watts: 0.050 free air Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55182/7 government specification Shelf Life: N/a Unit Of Measure:	
Inclosure Method: Encapsulated Terminal Type: Wire lead Mili-std-1276 Wire Lead Type Designator: C Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: Between 0.994 inches and 1.516 inches Body Diameter: Between 0.050 inches and 0.080 inches Body Length: 0.150 inches Power Dissipation Rating In Watts: 0.050 free air Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55182/7 government specification Shelf Life: N/a Unit Of Measure:	
Encapsulated Terminal Type: Wire lead Mil-std-1276 Wire Lead Type Designator: C Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: Between 0.984 inches and 1.516 inches Boddy Diameter: Between 0.984 inches and 0.880 inches Boddy Length: 0.150 inches Power Dissipation Rating In Watts: 0.050 free air Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55182/7 government specification Shelf Life: N/a Unit Of Measure:	
Terminal Type:  Wire lead  Mil-std-1276 Wire Lead Type Designator:  C  Reliability Indicator: Established  Reliability Failure Rate Level In Percent: 0.001  Terminal Length: Between 0.984 inches and 1.516 inches  Body Diameter: Between 0.980 inches and 0.080 inches  Body Length: 0.150 inches  Power Dissipation Rating In Watts: 0.050 free air  Test Data Document:  181349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-551827 government specification  Sheft Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	
Wire lead  Mil-std-1276 Wire Lead Type Designator:  C  Reliability Indicator: Established  Reliability Failure Rate Level In Percent: 0.001  Terminal Length: Between 0.984 inches and 1.516 inches  Body Diameter: Between 0.050 inches and 0.080 inches  Body Length: 0.150 inches  Power Dissipation Rating In Watts: 0.050 free air  Test Data Document:  81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-55182/7 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: Between 0.984 inches and 1.516 inches Body Diameter: Between 0.050 inches and 0.080 inches Body Length: 0.150 inches Power Dissipation Rating In Watts: 0.050 free air Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55182/7 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: Between 0.984 inches and 1.516 inches Body Diameter: Between 0.050 inches and 0.080 inches Body Length: 0.150 inches Power Dissipation Rating In Watts: 0.050 free air Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55182/7 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Mil-std-1276 Wire Lead Type Designator:
Established  Reliability Failure Rate Level In Percent:  0.001  Terminal Length:  Between 0.984 inches and 1.516 inches  Body Diameter:  Between 0.050 inches and 0.080 inches  Body Length:  0.150 inches  Power Dissipation Rating In Watts:  0.050 free air  Test Data Document:  81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-55182/7 government specification  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	
Reliability Failure Rate Level In Percent:  0.001  Terminal Length: Between 0.984 inches and 1.516 inches  Body Diameter: Between 0.050 inches and 0.080 inches  Body Length: 0.150 inches  Power Dissipation Rating In Watts: 0.050 free air  Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-55182/7 government specification  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No Fig:	Reliability Indicator:
Terminal Length: Between 0.984 inches and 1.516 inches  Body Diameter: Between 0.050 inches and 0.080 inches  Body Length: 0.150 inches  Power Dissipation Rating In Watts: 0.050 free air  Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-55182/7 government specification  Shelf Life: N/a  Unit Of Measure: Demilitarization: No Fig:	Established
Terminal Length: Between 0.984 inches and 1.516 inches  Body Diameter: Between 0.050 inches and 0.080 inches  Body Length: 0.150 inches  Power Dissipation Rating In Watts: 0.050 free air  Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-55182/7 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fitig:	Reliability Failure Rate Level In Percent:
Between 0.984 inches and 1.516 inches  Body Diameter:  Between 0.050 inches and 0.080 inches  Body Length: 0.150 inches  Power Dissipation Rating In Watts: 0.050 free air  Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-55182/7 government specification  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	0.001
Between 0.050 inches and 0.080 inches  Body Length: 0.150 inches  Power Dissipation Rating In Watts: 0.050 free air  Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-55182/7 government specification  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	Terminal Length:
Between 0.050 inches and 0.080 inches  Body Length: 0.150 inches  Power Dissipation Rating In Watts: 0.050 free air  Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-55182/7 government specification  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	Between 0.984 inches and 1.516 inches
Body Length:  0.150 inches  Power Dissipation Rating In Watts: 0.050 free air  Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-55182/7 government specification  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	Body Diameter:
O.150 inches  Power Dissipation Rating In Watts: O.050 free air  Test Data Document:  81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-55182/7 government specification  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	Between 0.050 inches and 0.080 inches
Power Dissipation Rating In Watts:  0.050 free air  Test Data Document:  81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-55182/7 government specification  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fitig:	Body Length:
O.050 free air  Test Data Document:  81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-55182/7 government specification  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	0.150 inches
Test Data Document:  81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-55182/7 government specification  Shelf Life: N/a  Unit Of Measure:   Demilitarization: No  Fiig:	Power Dissipation Rating In Watts:
81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-55182/7 government specification  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	0.050 free air
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-55182/7 government specification  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-55182/7 government specification  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Specification Data: 81349-mil-r-55182/7 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
81349-mil-r-55182/7 government specification  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Specification Data:
N/a Unit Of Measure: Demilitarization: No Fiig:	81349-mil-r-55182/7 government specification
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization:  No  Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0