NSN 5905-01-441-2449

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-441-2449

Resistance Tolerance In Percent: -2.000/42.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Inclosure Method: Encapsulated Terminal Type: Wire Isaad Millisatd-1276 Wire Lead Type Designator: C Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: Between 0.300 inches and 0.336 inches Body Length: Between 0.484 inches and 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mili-739017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similiar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mili-33017/4 government specification Shelf Life: Na Unit Of Measure: Cemilitarization: No	Electrical Resistance:
Resistance Tolerance in Percent: 2.000/+2.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Mil-std-1276 Wire Lead Type Designator: C Reliability Indicator: Established Reliability Failure Rate Level in Percent: 0.001 Body Diameter: Between 0.300 inches and 0.336 inches Body Length: Between 0.488 inches and 0.728 inches Power Dissipation Rating in Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: B1349-mil-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: B1349-mil-390174 government specification Shelf Life: Na Unit Of Measure: Demilitarization: No	
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Inclosure Method: Encapsulated Terminal Type: Write lead Mil-std-1276 Wire Lead Type Designator: C Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: Between 0.300 inches and 0.336 inches Body Length: Between 0.488 inches and 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mil-r-390174 government specification Shelf Life: Na Unit Of Measure:	
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Millisad-1276 Wire Lead Type Designator: C Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: Between 0.300 inches and 0.336 inches Body Length: Between 0.648 inches and 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mil390174 government specification Shelf Life: Na Unit Of Measure:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Mill-std-1276 Wire Lead Type Designator: C Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: Between 0.300 inches and 0.336 inches Body Length: Between 0.848 inches and 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: B1349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: B1349-mil-r-39017/4 government specification Shelf Life: N/a Unit Of Measure:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Inclosure Method: Encapsulated Terrinal Type: Wrire lead Mil-std-1276 Wire Lead Type Designator: C Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: Between 0.300 inches and 0.336 inches Body Length: Between 0.300 inches and 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/4 government specification Shelf Life: No Unit Of Measure:	
Inclosure Method: Encapsulated Terminal Type: Wire lead Mil-std-1276 Wire Lead Type Designator: C Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: Between 0.300 inches and 0.336 inches Body Length: Between 0.408 inches and 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: B1349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: B1349-mil-r-39017/4 government specification Sheft Life: N/a Unit Of Measure:	
Inclosure Method: Encapsulated Terminal Type: Wire lead Mil-std-1276 Wire Lead Type Designator: C Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: Between 0.300 inches and 0.336 inches Bedween 0.300 inches and 0.728 inches Bedween 0.300 inches and 0.728 inches Body Length: Between 0.648 inches and 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-milr-39017/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Encapsulated Terminal Type: Wire lead Mill-std-1276 Wire Lead Type Designator: C Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: Between 0.300 inches and 0.336 inches Body Length: Between 0.484 inches and 0.728 inches Body Length: Between 0.648 inches and 0.728 inches Power Dissipation Rating in Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: Bal349-milr-739017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: B1349-milr-39017/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Terminal Type: Wire lead Mill-std-1276 Wire Lead Type Designator: C Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: Between 0.300 inches and 0.336 inches Body Length: Between 0.408 inches and 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mill-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "*, etc.). Specification Data: 31349-mill-r-39017/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Wire lead Mil-std-1276 Wire Lead Type Designator: C Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: Between 0.300 inches and 0.336 inches Body Length: Between 0.648 inches and 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/4 government specification Sheelf Life: N/a Unit Of Measure: Demilitarization: No	
C Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: Between 0.300 inches and 0.336 inches Body Length: Between 0.648 inches and 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/4 government specification Shelf Life: N/a Unit Of Measure:	Wire lead
C Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: Between 0.300 inches and 0.336 inches Body Length: Between 0.648 inches and 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/4 government specification Shelf Life: N/a Unit Of Measure:	Mil-std-1276 Wire Lead Type Designator:
Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: Between 0.300 inches and 0.336 inches Body Length: Between 0.648 inches and 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	C
Reliability Failure Rate Level In Percent: 0.001 Body Diameter: Between 0.300 inches and 0.336 inches Body Length: Between 0.648 inches and 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	Reliability Indicator:
Body Diameter: Between 0.300 inches and 0.336 inches Body Length: Between 0.648 inches and 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	Established
Body Diameter: Between 0.300 inches and 0.336 inches Body Length: Between 0.648 inches and 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	Reliability Failure Rate Level In Percent:
Between 0.300 inches and 0.336 inches Body Length: Between 0.648 inches and 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	0.001
Between 0.648 inches and 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	Body Diameter:
Between 0.648 inches and 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	Between 0.300 inches and 0.336 inches
Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	Body Length:
2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	Between 0.648 inches and 0.728 inches
Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	Power Dissipation Rating In Watts:
Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	2.000 free air
Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	Style Designator:
81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	Axial terminal each end
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	Test Data Document:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Specification Data: 81349-mil-r-39017/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
81349-mil-r-39017/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life: N/a Unit Of Measure: Demilitarization: No	Specification Data:
N/a Unit Of Measure: Demilitarization:	81349-mil-r-39017/4 government specification
Unit Of Measure: Demilitarization: No	Shelf Life:
 Demilitarization: No	N/a
No	Unit Of Measure:
No	
	Demilitarization:
Fiig:	No
	Fiig:
A001a0	A001a0