Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-442-5018

## **Electrical Resistance:**

294.000 ohms

**Resistance Tolerance In Percent:** 

-1.000/+1.000

Ambient Tempurature In Deg Celsius At Full Rated Power:

25.0

Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

275.0

**Inclosure Method:** 

Uninclosed

Terminal Type:

Tab, solder lug

**Reliability Indicator:** 

Established

Reliability Failure Rate Level In Percent:

0.010

Body Length:

Between 0.688 inches and 0.812 inches

**Body Width:** 

Between 0.376 inches and 0.500 inches

**Body Height:** 

Between 0.375 inches and 0.437 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 0.552 inches and 0.572 inches

**Power Dissipation Rating In Watts:** 

6.000 free air

Mounting Hole Size:

Between 0.089 inches and 0.099 inches

## Style Designator:

Axial terminal (s)

## **Test Data Document:**

81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-r-39009/2 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A001a0