Noninductive Wire Wound Fixed Resistor - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5905-01-445-2290



### **Electrical Resistance:**

2.560 kilohms

### **Resistance Tolerance In Percent:**

-0.050/+0.050

## Ambient Tempurature In Deg Celsius At Full Rated Power:

125.0

## Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

145.0

### **Inclosure Method:**

Encapsulated

### **Terminal Type:**

Wire lead

### **Reliability Indicator:**

Established

Reliability Failure Rate Level In Percent:

0.010

# Body Diameter:

Between 0.360 inches and 0.390 inches

### Body Length:

Between 0.718 inches and 0.770 inches

# **Power Dissipation Rating In Watts:**

0.333 free air

## Style Designator:

Axial terminal each end

### **Test Data Document:**

81349-mil-r-39005 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Specification Data:**

81349-mil-r-39005/2 government specification

### Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

No

# Fiig:

A001a0