## NSN 5905-01-445-2326

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-445-2326

Electrical Resistance:
1.022 kilohms
Resistance Tolerance In Percent:
-0.050/+0.050 Ambient Tempurature In Deg Coleius At Full Peted Bower.
Ambient Tempurature In Deg Celsius At Full Rated Power:
125.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
145.0
Inclosure Method:
Encapsulated  Torminal Tymes
Terminal Type:
Wire lead
Reliability Indicator:
Established  Reliabilities Fallows Resta Local In Research
Reliability Failure Rate Level In Percent:
0.010
Body Diameter:
Between 0.235 inches and 0.265 inches
Body Length:
Between 0.468 inches and 0.520 inches
Power Dissipation Rating In Watts:
0.150 free air
Style Designator:
Axial terminal each end
Test Data Document:
81349-mil-r-39005 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-r-39005/4 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No Eller
Fiig:
A001a0