Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-445-3040

## **Electrical Resistance:**

37.500 kilohms

**Resistance Tolerance In Percent:** 

-0.010/+0.010

Ambient Tempurature In Deg Celsius At Full Rated Power:

125.0

Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

145.0

**Inclosure Method:** 

Encapsulated

Terminal Type:

Wire lead

**Reliability Indicator:** 

Established

Reliability Failure Rate Level In Percent:

0.010

Body Diameter:

Between 0.235 inches and 0.265 inches

**Body Length:** 

Between 0.468 inches and 0.520 inches

## **Power Dissipation Rating In Watts:**

0.150 free air

Style Designator:

Axial terminal each end

## **Test Data Document:**

81349-mil-r-39005 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-r-39005/4 government specification

Shelf Life:

N/a

Unit Of Measure:

---

**Demilitarization:** 

No

Fiig:

A001a0