## NSN 5905-01-445-4622

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-445-4622

| Electrical Resistance:   |
|--|
| 17.000 ohms  |
| Resistance Tolerance In Percent:   |
| -0.100/+0.100  |
| Ambient Tempurature In Deg Celsius At Full Rated Power:  |
| 25.0   |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  |
| 275.0  |
| Inclosure Method:  |
| Encapsulated Encapsulated  |
| Terminal Type:   |
| Wire lead  |
| Reliability Indicator:   |
| Established  |
| Reliability Failure Rate Level In Percent:   |
| 0.010  |
| Body Diameter:   |
| Between 0.156 inches and 0.218 inches  |
| Body Length:   |
| Between 0.498 inches and 0.622 inches  |
| Power Dissipation Rating In Watts:   |
| 3.000 free air   |
| Style Designator:  |
| Axial terminal each end  |
| Test Data Document:  |
| 81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Specification Data:  |
| 81349-mil-r-39007/11 government specification  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <del></del>  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A001a0   |
|  |