NSN 5905-01-451-0226

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-451-0226

Electrical Kesistance: 1,10004-1,000 Ambient Tempurature In Deg Celsius At Full Rated Power: 7,00 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150,0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150,0 Inclosure Method: Uninclosed Terminal Type: Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0,010 Body Length: 1,6 millimeters Body Width: 3,2 millimeters Body Width: 3,2 millimeters Body Width: 1,0 millimeters Body Height: 1,0 millimeters Fower Dissipation Rating In Watts: 0,250 free air Style Designator: Termination pad each end Test Data Document: 8,1349-mill-5,5342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 8,1349-mill-5,5342/7 government specification Shelf Life: Na Unit Of Measure: — Demilitarization: No Filig: A001-80	
Resistance Tolerance In Percent: -1.0004-1.0000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Inclosure Method: Uniciosed Terminal Type: Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Beddy Length: 1.6 millimeters Body Width: 2.2 millimeters Body Width: 2.2 millimeters Body Height: 1.0 millimeters Power Dissipation Rating In Watts: 0.250 free air Style Designator: Terminality pad each end Test Data Document: 81349-mill-r55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, inclustry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mill-r55342/7 government specification No Demilitarization: No Demilitarization: No Flig:	Electrical Resistance:
Anbient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Inclosure Method: Uninclosed Terminal Type: Terminal Type: Terminal type per body style Reliability Indicator: Established Reliability Fallure Rate Level In Percent: 0.010 Body Length: 1.6 millimeters Body Width: 3.2 millimeters Body Height: 1.0 millimeters Power Dissipation Rating In Watts: 0.250 free air Style Designator: Terminaltop ad each end Test Data Document: 81349-mil-7-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-7-55342/7 government specification Shelf Life: Na Unit Of Measure:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Inclosure Method: Uninclosed Terminal Type: Terminal Type: Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Length: 1.6 millimeters Body Width: 3.2 millimeters Body Width: 3.2 millimeters Body Height: 1.0 millimeters Power Dissipation Rating In Watts: 0.250 free air Style Designator: Terminalton pad each end Test Data Document: 81349-mill-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mill-553427 government specification Sheff Life: N/a Unit Of Measure: Domilitarization: No Filig:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Inclosure Method: Uninclosed Terminal Type: Terminal Type: Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Length: 1.6 millimeters Body Width: 3.2 millimeters Body Width: 3.2 millimeters Power Dissipation Rating In Watts: 0.250 free air Style Designator: Termination pad each end Test Data Document: B14349-mill-75342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: B1349-mill-753427 government specification Sheff Life: N/a Unit Of Measure:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Inclosure Method: Uninclosed Terminal Type: Terminal Type: Terminal Type: Terminal Upe per body style Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Length: 1.6 millimeters Body Width: 3.2 millimeters Body Wight: 1.0 millimeters Body Height: 1.0 millimeters Power Dissipation Rating In Watts: 0.250 free air Style Designator: Terminalton pad each end Terminalton pad each end Termination pad each end end: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mil-r-553427 government specification Shelf Life: N/a Unit Of Measure:	
Inclosure Method: Uninclosed Terminal Type: Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level in Percent: 0.010 Body Length: 1.6 millimeters Body Width: 3.2 millimeters Body Height: 1.0 millimeters Power Dissipation Rating in Watts: 0.250 free air Style Designator: Termination pad each end Test Data Document: 81349-mill-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/7 government specification Shelf Life: N/a Unit Of Measure:	
Inciciosure Method: Uninciosed Terminal Type: Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Length: 1.6 millimeters Body Width: 3.2 millimeters Body Height: 1.0 millimeters Body Height: 1.0 millimeters Body Height: 1.10 millimeters Bo	
Uninclosed Terminal Type: Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Length: 1.6 millimeters Body Witth: 3.2 millimeters Body Height: 1.0 millimeters Body Height: 1.0 millimeters Power Dissipation Rating In Watts: 0.250 free air Style Designator: Termination pad each end Test Data Document: Briang-millimeters and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mill-r-55342/7 government specification Sheft Life: N/a Unit Of Measure:	150.0
Terminal type: Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level in Percent: 0.010 Body Length: 1.6 millimeters Body Width: 3.2 millimeters Body Height: 1.0 millimeters Power Dissipation Rating in Watts: 0.250 free air Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-553427 government specification Sheft Life: N/a Unit Of Measure: — Demilitarization: No Fiig:	Inclosure Method:
Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Length: 1.6 millimeters Body Width: 3.2 millimeters Body Height: 1.0 millimeters Body Height: 1.0 millimeters Power Dissipation Rating In Watts: 0.250 free air Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/7 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Uninclosed
Reliability Indicator: Established Reliability Failure Rate Level In Percent:	Terminal Type:
Established Reliability Failure Rate Level In Percent: 0.010 Body Length: 1.6 millimeters Body Width: 3.2 millimeters Body Height: 1.0 millimeters Power Dissipation Rating In Watts: 0.250 free air Style Designator: Termination pad each end Test Data Document: 81349-mill-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/7 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminal type per body style
Reliability Failure Rate Level In Percent: 0.010 Body Length: 1.6 millimeters Body Width: 3.2 millimeters Body Height: 1.0 millimeters Body Height: 1.0 millimeters Power Dissipation Rating In Watts: 0.250 free air Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/7 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Reliability Indicator:
Body Length: 1.6 millimeters Body Width: 3.2 millimeters Body Height: 1.0 millimeters Power Dissipation Rating In Watts: 0.250 free air Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/7 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Established
Body Length: 1.6 millimeters Body Width: 3.2 millimeters Body Height: 1.0 millimeters Power Dissipation Rating In Watts: 0.250 free air Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/7 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Reliability Failure Rate Level In Percent:
1.6 millimeters Body Width: 3.2 millimeters Body Height: 1.0 millimeters Power Dissipation Rating In Watts: 0.250 free air Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/7 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.010
Body Width: 3.2 millimeters Body Height: 1.0 millimeters Power Dissipation Rating In Watts: 0.250 free air Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/7 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Length:
3.2 millimeters Body Height: 1.0 millimeters Power Dissipation Rating In Watts: 0.250 free air Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/7 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	1.6 millimeters
Body Height: 1.0 millimeters Power Dissipation Rating In Watts: 0.250 free air Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/7 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Width:
1.0 millimeters Power Dissipation Rating In Watts: 0.250 free air Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/7 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	3.2 millimeters
Power Dissipation Rating In Watts: 0.250 free air Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/7 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Height:
Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/7 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	1.0 millimeters
Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/7 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fitig:	Power Dissipation Rating In Watts:
Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/7 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.250 free air
Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/7 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/7 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Termination pad each end
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/7 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/7 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Specification Data: 81349-mil-r-55342/7 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
81349-mil-r-55342/7 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Specification Data:
N/a Unit Of Measure: Demilitarization: No Fiig:	81349-mil-r-55342/7 government specification
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0