NSN 5905-01-451-3159

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-451-3159

Electrical Resistance: 0.090 kilohms Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Mil-std-1276 Wire Lead Type Designator: Celsiability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: Between 0.344 inches and 0.437 inches Body Length: Between 1.000 inches and 1.124 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Avial terminal each end Test Data Document:
Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Mil-std-1276 Wire Lead Type Designator: Cereliability Indicator: Established Reliability Failure Rate Level In Percent: 20.001 20.001 20.001 20.001 20.002 20.003 20.003 20.004 Length: 20.004 Length: 20.005 Length: 20.005 Length: 20.006 Length: 20.006 Length: 20.007 Length: 20.007 Length: 20.008 Length: 20.009 Length: 20
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Mil-std-1276 Wire Lead Type Designator: Celleability Indicator: Established Reliability Failure Rate Level In Percent: 20.001 Body Diameter: Between 0.344 inches and 0.437 inches Body Length: Between 1.000 inches and 1.124 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Mil-std-1276 Wire Lead Type Designator: Celliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: Between 0.344 inches and 0.437 inches Body Length: Between 1.000 inches and 1.124 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Mil-std-1276 Wire Lead Type Designator: C. Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: Between 0.344 inches and 0.437 inches Between 1.000 inches and 1.124 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Mil-std-1276 Wire Lead Type Designator: C Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: Between 0.344 inches and 0.437 inches Body Length: Between 1.000 inches and 1.124 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end
Inclosure Method: Encapsulated Terminal Type: Wire lead Mil-std-1276 Wire Lead Type Designator: C Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: Between 0.344 inches and 0.437 inches Body Length: Between 1.000 inches and 1.124 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end
Inclosure Method: Encapsulated Ferminal Type: Wire lead Mil-std-1276 Wire Lead Type Designator: C Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: Between 0.344 inches and 0.437 inches Body Length: Between 1.000 inches and 1.124 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end
Encapsulated Terminal Type: Wire lead Mil-std-1276 Wire Lead Type Designator: C Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: Between 0.344 inches and 0.437 inches Body Length: Between 1.000 inches and 1.124 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end
Mire lead Mil-std-1276 Wire Lead Type Designator: C Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: Between 0.344 inches and 0.437 inches Body Length: Between 1.000 inches and 1.124 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end
Wire lead Mil-std-1276 Wire Lead Type Designator: C Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: Between 0.344 inches and 0.437 inches Body Length: Between 1.000 inches and 1.124 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end
Mil-std-1276 Wire Lead Type Designator: C Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: Between 0.344 inches and 0.437 inches Body Length: Between 1.000 inches and 1.124 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: Between 0.344 inches and 0.437 inches Body Length: Between 1.000 inches and 1.124 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: Between 0.344 inches and 0.437 inches Body Length: Between 1.000 inches and 1.124 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end
Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: Between 0.344 inches and 0.437 inches Body Length: Between 1.000 inches and 1.124 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end
Reliability Failure Rate Level In Percent: 0.001 Body Diameter: Between 0.344 inches and 0.437 inches Body Length: Between 1.000 inches and 1.124 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end
Body Diameter: Between 0.344 inches and 0.437 inches Body Length: Between 1.000 inches and 1.124 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end
Body Diameter: Between 0.344 inches and 0.437 inches Body Length: Between 1.000 inches and 1.124 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end
Between 0.344 inches and 0.437 inches Body Length: Between 1.000 inches and 1.124 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end
Body Length: Between 1.000 inches and 1.124 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end
Between 1.000 inches and 1.124 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end
Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end
1.000 free air Style Designator: Axial terminal each end
Style Designator: Axial terminal each end
Axial terminal each end
31349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
31349-mil-r-55182/10 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A001a0