## NSN 5905-01-452-5238

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-452-5238

Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: -7.00 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: -7.00 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: -7.00 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: -7.00 -7.	Electrical Resistance:
Resistance Tolerance in Percent: 1.0004-1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Inclosure Method: Uninclosed Terminal Type: Terminal Type: Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Length: 0.056 inches Body Width: 0.056 inches Body Width: 0.075 inches Body Height: Between 0.010 inches and 0.040 inches Power Dissipation Rating in Watts: 0.100 free air Style Designator: Termination pad each end Test Data Document: 81345-mill-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81345-mill-r-5534276 government specification No Pilig: Unit Of Measure:	
Anbient Tempurature In Deg Celaius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celaius At Zero Percent Rated Power: 150.0 Inclosure Method: Uninclosed Terminal Type: Terminal Type: Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Length: 0.050 inches Body Width: 0.050 inches Body Width: 0.075 inches Body Height: Between 0.010 inches and 0.040 inches Power Dissipation Rating in Watts: 0.100 free air Style Designator: Termination pad each end Test Data Document: Style Designator: Termination pad each end Test Data Document: Style Designator: Termination pad each end Test Data Document: Style Designator: Termination pad each end Test Data Document: Style Designator: Termination pad each end Test Data Document: Style Designator: Termination pad each end Test Data Document: Style Designator: Termination pad each end Test Data Document: Style Designator: Termination pad each end Test Data Document: Style Designator: Termination pad each end Test Data Document: Style Designator: Termination pad each end Test Data Document: Style Designator: Termination pad each end Test Data Document: Style Designator: Termination pad each end Test Data Document: Style Designator: Termination pad each end Test Data Document: Style Designator: Termination pad each end Test Data Document: Style Designator: Termination pad each end Test Data Document: Style Designator: Termination pad each end Test Data Document: Style Designator: Termination pad each end Test Data Document: Termination pad each end Test Data Data Data	
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Inclosure Method: Uninclosed Terminal Type: Uninclosed Terminal Type: Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Length: 0.050 inches Body Wildth: 0.075 inches Body Wildth: 0.075 inches Body Height: Between 0.101 inches and 0.040 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Terminalton pad each end Test Data Document: 81349-mill-755342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 181349-mill-755342 government specification Sheff Life: N/a Unit Of Measure:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0 Inclosure Method: Uninciosed Terminal Type: Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Length: 0.050 inches Body Wildt: 0.075 inches Body Wildt: 0.075 inches Body Wildt: 0.075 inches Body Height: Between 0.101 inches and 0.040 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Terminaliton pad each end Test Data Document: B1349-mil+-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: B1349-mil+-55342/6 government specification Shelf Life: N/a Unit Of Measure:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0 Inclosure Method: Uninclosed Terminal Type: Terminal Type: Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Length: 0.050 inches Body Width: 0.050 inches Body Width: 0.050 inches Body Width: 0.075 inches Body Height: Bettween 0.010 inches and 0.040 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Terminalton pad each end Ters Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mil-r-55342/6 government specification Shelf Life: N/a Unit Of Measure:	
Inclosure Method: Uninclosed Terminal Type: Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Length: 0.050 inches Body Width: 0.075 inches Body Width: 0.075 inches Body Height: Bettween 0.010 inches and 0.040 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Termination pad each end Test Data Document: B1349-mill-r55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: B1349-mill-r-55342/6 government specification Shelf Life: N/a Unit Of Measure:	
Inciosure Method: Uninciosed Terminal Type: Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Length: 0.050 inches Body Width: 0.075 inches Body Width: 0.075 inches Body Height: Between 0.010 inches and 0.040 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Termination pad each end Test Data Document: B1349-mil-r-55342 specification (includes engineering type builletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: B1349-mil-r-55342/6 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	
Uninclosed Terminal Type: Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Length: 0.050 inches Body Width: 0.055 inches Body Width: 0.075 inches Body Height: Between 0.010 inches and 0.040 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Termination pad each end Test Data Document: Style Designator: Style Designator: Termination pad each end Test Data Document: Bi 1349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: Bi 1349-mil-r-55342/f6 government specification Shelf Life: No Unit Of Measure:	
Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level in Percent: 0.001 Body Length: 0.050 inches Body Width: 0.055 inches Body Width: 0.075 inches Body Height: Between 0.010 inches and 0.040 inches Power Dissipation Rating in Watts: 0.100 free air Style Designator: Termination pad each end Test Data Document: Bri349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "', etc.). Specification Data: 81349-mil-r-55342/6 government specification Sheft Life: N/a Unit Of Measure:	
Terminal type per body style  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  0.001  Body Length: 0.050 inches  Body Width: 0.075 inches  Body Height:  Between 0.010 inches and 0.040 inches  Power Dissipation Rating In Watts: 0.100 free air  Style Designator:  Termination pad each end  Test Data Document:  81349-milr-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-milr-55342/6 government specification  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Flig:	
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Length: 0.056 inches Body Width: 0.075 inches Body Height: Between 0.010 inches and 0.040 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Termination pad each end Test Data Document: 81349-milr-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "*, etc.). Specification Data: 81349-milr-55342/6 government specification Shelf Life: N/a Unit Of Measure:	
Established  Reliability Failure Rate Level In Percent:  0.0001  Body Length: 0.050 inches  Body Width: 0.075 inches  Body Height: Between 0.010 inches and 0.040 inches  Power Dissipation Rating In Watts: 0.100 free air  Style Designator: Termination pad each end  Test Data Document:  81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-55342/6 government specification  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Flig:	
Body Length: 0.050 inches Body Width: 0.075 inches Body Height: Between 0.010 inches and 0.040 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Termination pad each end Test Data Document: B1349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: B1349-mil-r-55342/6 government specification Shelf Life: N/a Unit Of Measure:	Established
Body Length: 0.050 inches Body Width: 0.075 inches Body Height: Between 0.010 inches and 0.040 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Termination pad each end Test Data Document: B1349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: B1349-mil-r-55342/6 government specification Shelf Life: N/a Unit Of Measure:	Reliability Failure Rate Level In Percent:
0.050 inches  Body Width: 0.075 inches  Body Height: Between 0.010 inches and 0.040 inches  Power Dissipation Rating In Watts: 0.100 free air  Style Designator: Termination pad each end  Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-55342/6 government specification  Shelf Life: N/a  Unit Of Measure: Demilitarization: No  Fig:	0.001
Body Width:  0.075 inches Body Height: Between 0.010 inches and 0.040 inches Power Dissipation Rating In Watts:  0.100 free air  Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-55342/6 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Length:
Body Height: Between 0.010 inches and 0.040 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/6 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.050 inches
Between 0.010 inches and 0.040 inches  Power Dissipation Rating In Watts: 0.100 free air  Style Designator: Termination pad each end  Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-55342/6 government specification  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	Body Width:
Between 0.010 inches and 0.040 inches  Power Dissipation Rating In Watts:  0.100 free air  Style Designator:  Termination pad each end  Test Data Document:  81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-55342/6 government specification  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	0.075 inches
Power Dissipation Rating In Watts:  0.100 free air  Style Designator: Termination pad each end  Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-55342/6 government specification  Shelf Life: N/a  Unit Of Measure: Demilitarization: No  Fiig:	Body Height:
Outloof free air  Style Designator: Termination pad each end Test Data Document:  81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-55342/6 government specification  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fig:	Between 0.010 inches and 0.040 inches
Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-55342/6 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
Termination pad each end  Test Data Document:  81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-55342/6 government specification  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	0.100 free air
Test Data Document:  81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-55342/6 government specification  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Style Designator:
81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-55342/6 government specification  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Termination pad each end
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-55342/6 government specification  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Test Data Document:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-55342/6 government specification  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Specification Data: 81349-mil-r-55342/6 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
81349-mil-r-55342/6 government specification  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Specification Data:
N/a Unit Of Measure: Demilitarization: No Filig:	81349-mil-r-55342/6 government specification
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0