## NSN 5905-01-452-9139

Precision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-452-9139 **Section Quantity:** 3 **Body Style:** Rectangular bushing mounted **Reliability Indicator:** Not established **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.520 inches **Mounting Stud Length:** 0.250 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.930 inches **Body Width:** 0.051 inches **Body Height:** 0.051 inches **Shaft Style:** Round **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Maximum Stop Torque:** 64.00 inch-ounces **End Application:** Coast guard hh-65a helicopter **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Facility Quantity:** 1 **Terminal Location:** Right-left adjacent sides

**Mounting Method:** 

Threaded stud

## NSN 5905-01-452-9139

Precision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
50.0 kilohms all sections
Rotary Actuator Travel In Angular Deg:
270.0
Power Dissipation Rating Per Section In Watts:
1.0 free air all sections
Resistance Tolerance Per Section In Percent:
-5.0/+2.0 single section
Actuator Travel Control Feature:
Stops
Terminal Type And Quantity:
9 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A00250