## NSN 5905-01-453-0155

**Fiig:** A001a0

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-453-0155

| Electrical Resistance:   |
|--|
| 250.000 ohms   |
| Resistance Tolerance In Percent:   |
| -1.000/+1.000  |
| Ambient Tempurature In Deg Celsius At Full Rated Power:  |
| 25.0   |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  |
| 275.0  |
| Inclosure Method:  |
| Uninclosed   |
| Terminal Type:   |
| Tab, solder lug  |
| Reliability Indicator:   |
| Established  |
| Reliability Failure Rate Level In Percent:   |
| 0.010  |
| Body Length:   |
| Between 0.538 inches and 0.662 inches  |
| Body Width:  |
| Between 0.272 inches and 0.396 inches  |
| Body Height:   |
| Between 0.289 inches and 0.351 inches  |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:   |
| Between 0.434 inches and 0.454 inches  |
| Power Dissipation Rating In Watts:   |
| 3.000 free air   |
| Mounting Hole Size:  |
| Between 0.088 inches and 0.098 inches  |
| Style Designator:  |
| Axial terminal (s)   |
| Test Data Document:  |
| 81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Specification Data:  |
| 81349-mil-r-39009/1 government specification   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <del></del>  |
| Demilitarization:  |
| No   |