NSN 5905-01-453-1096

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-453-1096

Electrical Resistance: 1.500 ohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Inclosure Method: Unincidesed Terminal Type: Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Length: 0.124 inches Body Wildth: 0.248 inches Body Height: 0.393 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Termination pad each end Test Data Document: 81349-mil-1-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-1-55342/9 government specification Sheff Life: Na Unit Of Measure: — Demilitarization: No Filig: A001a0	Floatrical Projetoway
Resistance Tolerance in Percent: -1.000/+1.000 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 70.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Inclosure Method: Uninclosaed Terminal Type: Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level in Percent: 0.001 Body Length: 0.124 inches Body Width: 0.248 inches Body Width: 0.289 inches Body Height: 0.039 inches Power Dissipation Rating in Watts: 1.000 free air Style Designator: Termination pad each end Test Data Document: B1349-mil-F-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: B1349-mil-F-55342/9 government specification Na Unit of Measure:	
-1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 7.0.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Inclosure Method: Uninclosed Terminal Type: Terminal Type: Terminal type per body style Reliability Indicator: Established Reliability Fallure Rate Level In Percent: 0.001 Body Length: 0.124 inches Body Width: 0.2248 inches Body Height: 0.039 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Terminaltop ad each end Test Data Document: 81349-mili-755342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mili-7553429 government specification Sheff Life: Na Unit Of Measure:	
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Inclosure Method: Uninclossed Terminal Type: Terminal Type: Terminal Type Poddy style Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Length: 0.124 inches Body Width: 0.248 inches Body Width: 0.248 inches Body Height: 0.039 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Terminalton pad each end Test Data Document: 81349-mill-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typicai", "average", "", etc.). Specification Data: 81349-mill-553429 government specification Sheff Life: Na Unit Of Measure: Demilitarization: No Filig:	
70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Inclosure Method: Uninclosed Terminal Type: Terminal type per body style Reliability Indicest: Established Reliability Failure Rate Level In Percent: 0.001 Body Length: 0.124 inches Body Width: 0.248 inches Body Width: 0.298 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Terminalton pad each end Test Data Document: 815439-mil-75342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-7-5342/9 government specification Sheff Life: Na Unit Of Measure: Demilitarization: No Filig:	
Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Inclosure Method: Uninclosed Terminal Type: Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Length: 0.124 inches Body Width: 0.228 inches Body Height: 0.039 inches Power Dissipation Rating in Watts: 1.000 ree air Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mil-r-55342/9 government specification Shelf Life: N/a Unit Of Measure:	
Inclosure Method: Uninclosed Terminal Type: Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level in Percent: 0.001 Body Length: 0.124 inches Body Width: 0.248 inches Body Width: 0.248 inches Body Height: 0.039 inches Power Dissipation Rating in Watts: 1.000 free air Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342; specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/9 government specification Shelf Life: N/a Unit Of Measure:	
Inclosure Method: Uninclosed Terminal Type: Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Length: 0.124 inches Body Width: 0.248 inches Body Width: 0.399 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Termination pad each end Test Data Document: 81349-milr-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-milr-55342/9 government specification Shelf Life: N/a Unit Of Measure:	
Uninclosed Terminal Type: Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Length: 0.124 inches Body Witth: 0.248 inches Body Witth: 0.039 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342/9 government specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/9 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	
Terminal type: Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Length: 0.124 inches Body Wildth: 0.248 inches Body Wildth: 0.28 inches Body Height: 0.099 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "', etc.). Specification Data: 81349-mil-r-55342/9 government specification Shelf Life: N/a Unit Of Measure:	
Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Length: 0.124 inches Body Width: 0.248 inches Body Height: 0.039 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/9 government specification Shelf Life: N/a Unit Of Measure:	
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Length: 0.124 inches Body Width: 0.248 inches Body Height: 0.039 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Termination pad each end Test Data Document: 81349-milr-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-milr-55342/9 government specification Shelf Life: No Unit Of Measure: Demilitarization: No Flig:	
Established Reliability Failure Rate Level In Percent: 0.001 Body Length: 0.124 inches Body Width: 0.248 inches Body Height: 0.039 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Termination pad each end Test Data Document: 81349-mill-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/9 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Reliability Failure Rate Level In Percent: 0.001 Body Length: 0.124 inches Body Width: 0.248 inches Body Height: 0.039 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/9 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	
Body Length: 0.124 inches Body Width: 0.248 inches Body Height: 0.039 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/9 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Body Length: 0.124 inches Body Width: 0.248 inches Body Height: 0.039 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/9 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
0.124 inches Body Width: 0.248 inches Body Height: 0.039 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/9 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Body Width: 0.248 inches Body Height: 0.039 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/9 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
0.248 inches Body Height: 0.039 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/9 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Body Height: 0.039 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/9 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
0.039 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/9 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Power Dissipation Rating In Watts: 1.000 free air Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/9 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
1.000 free air Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/9 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/9 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/9 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/9 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/9 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/9 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/9 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Specification Data: 81349-mil-r-55342/9 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
81349-mil-r-55342/9 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
N/a Unit Of Measure: Demilitarization: No Fiig:	
Unit Of Measure: Demilitarization: No Fiig:	
Demilitarization: No Fiig:	
No Fiig:	
No Fiig:	Demilitarization:
Fiig:	