NSN 5905-01-453-1652

Precision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-453-1652

Seedien Overditus
Section Quantity:
1 Parks Of stars
Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Not established
Terminal Length:
0.200 inches
Mounting Hole Diameter:
0.093 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.750 inches
Body Length:
2.000 inches
Body Width:
Between 0.370 inches and 0.380 inches
Body Height:
0.500 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Distance Between Mounting Hole Centers:
0.250 inches
End Application:
Ttu 373 test set
Lateral Distance Between Mounting Hole Centers:
1.800 inches
Mounting Facility Quantity:
4
Terminal Location:
Left adjacent side single row
Mounting Method:
Unthreaded hole
Electrical Resistance Per Section:
20.0 kilohms single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0/+50.0 single section
Power Dissipation Rating Per Section In Watts:

2.0 free air single section

NSN 5905-01-453-1652

No Fiig: A002a0

Precision Nonwire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section Special Features: Aluminum housing, retractable shaft Terminal Type And Quantity: 3 turret Shelf Life: N/a Unit Of Measure: - Demilitarization: