Precision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-453-1653

Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

Reliability Indicator:

Not established

Terminal Length:

0.200 inches

Mounting Hole Diameter:

0.093 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.750 inches

Body Length:

3.000 inches

Body Width:

Between 0.370 inches and 0.380 inches

Body Height:

0.500 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Distance Between Mounting Hole Centers:

0.250 inches

End Application:

Ttu373 test set

Lateral Distance Between Mounting Hole Centers:

2.800 inches

Mounting Facility Quantity:

4

Terminal Location:

Left adjacent side single row

Mounting Method:

Unthreaded hole

Electrical Resistance Per Section:

40.0 kilohms single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

NSN 5905-01-453-1653

Precision Nonwire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Special Features:

Aluminum housing; retractable shaft

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0