## NSN 5905-01-453-2952

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-453-2952

Electrical Resistance: 4.750 megohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Inclosure Method: Uninclosed Terminal Type: Terminal type per body style Retiability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Longth: 1.4 millimeters Body Width: 3.2 millimeters Body Height: 1.0 millimeters Body Height: 1.1 millimeters Body Basinator: Terminal Type generating in Watts: 0.250 free air Style Designator: Termination pad each end Test Data Document: 181349-mill-5342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mill-53427 government specification Shelf Life: Na Unit of Measure:	
Resistance Tolerance in Percent:  -1.000/-1.000 Ambient Tempurature in Deg Celsius At Full Rated Power:  70.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power:  150.0 Inclosure Method: Uninclosed Terminal Type: Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level in Percent:  0.001 Body Length: 1.4 millimeters Body Width: 3.2 millimeters Body Width: 3.2 millimeters Body Height: 1.0 millimeters Power Dissipation Rating in Watts: 0.250 free air Style Designator: Termination pad each end Test Data Document: B1349-mill-65342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "everage", ", etc.). Specification Data: B1349-mill-65342/7 government specification Specification State:  No Bullitarization: No Filig:	Electrical Resistance:
-1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Inclosure Method: Uninclosed Terminal Type: Terminal Type: Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Length: 1.4 millimeters Body Width: 3.2 millimeters Body Width: 3.2 millimeters Body Height: 1.0 millimeters Power Dissipation Rating In Watts: 0.250 free air Style Designator: Termination pad each end Tost Data Document: 81349-mil-7-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 181349-mil-7-55342/7 government specification Shelf Life: No Unit Of Measure:	4.750 megohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Inclosure Method: Uninclossed Terminal Type: Terminal type per body style Reliability Indicator: Established Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Length: 1.4 millimeters Body Width: 3.2 millimeters Body Width: 3.2 millimeters Body Height: 1.0 millimeters Power Dissipation Rating In Watts: 0.250 free air Style Designator: Termination pad each end Test Data Document: 81349-mill-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mill-55342/7 government specification Sheff Life: Na Unit Of Measure: Demilitarization: No Filig:	Resistance Tolerance In Percent:
70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Inclosure Method: Uninclosed Terminal Type: Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Length: 1.4 millimeters Body Width: 3.2 millimeters Body Width: 3.2 millimeters Power Dissipation Rating In Watts: 0.250 free air Style Designator: Terminal top ad each end Test Data Document: B15439-mill-r55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similiar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: B1349-mill-r55342/7 government specification Sheft Life: Na Unit Of Measure: Demilitarization: No Filig:	-1.000/+1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0 Inclosure Method: Uninclosed Terminal Type: Terminal type: Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Length: 1.4 millimeters Body Width: 3.2 millimeters Body Width: 3.2 millimeters Body Height: 1.0 millimeters Power Dissipation Rating In Watts: 0.250 free air Style Designator: Termination pad each end Terminal type specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average*, ", etc.). Specification Data: 81349-mil-F553427 government specification Shelf Life: N/a Unit Of Measure:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Inclosure Method: Uninclosed Terminal Type: Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Length: 1.4 millimeters Body Width: 3.2 millimeters Body Width: 3.2 millimeters Body Height: 1.0 millimeters Power Dissipation Rating In Watts: 0.250 free air Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-553427 government specification Shelf Life: N/a Unit Of Measure:	70.0
Inclosure Method: Uninclosed Terminal Type: Terminal Type per body style Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Length: 1.4 millimeters Body Width: 3.2 millimeters Body Width: 3.7 millimeters Body Height: 1.0 millimeters Power Dissipation Rating In Watts: 0.250 free air Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-553427 government specification Shelf Life: N/a Unit Of Measure:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Uninclosed Terminal Type: Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Length: 1.4 millimeters Body Width: 3.2 millimeters Body Width: 1.1 o millimeters Body Height: 1.0 millimeters Power Dissipation Rating In Watts: 0.250 free air Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/7 government specification Sheft Life: N/a Unit Of Measure: Demilitarization: No Flig:	150.0
Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Length: 1.4 millimeters Body Width: 3.2 millimeters Body Height: 1.0 millimeters Power Dissipation Rating In Watts: 0.250 free air Style Designator: Termination pad each end Test Data Document: 81349-mil55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil553427 government specification Shelf Life: N/a Unit Of Measure:	Inclosure Method:
Terminal type per body style  Reliability Indicator: Established  Reliability Failure Rate Level In Percent: 0.001  Body Length: 1.4 millimeters  Body Width: 3.2 millimeters  Body Height: 1.0 millimeters  Body Height: 1.0 millimeters  Power Dissipation Rating In Watts: 0.250 free air  Style Designator: Termination pad each end  Test Data Document:  81 349-mill-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81 349-mill-r-55342/7 government specification  Shelf Life:  No  Unit Of Measure:   Demilitarization:  No  Flig:	Uninclosed
Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  0.001  Body Length: 1.4 millimeters  Body Width: 3.2 millimeters  Body Height: 1.0 millimeters  Power Dissipation Rating In Watts: 0.250 free air  Style Designator: Termination pad each end  Test Data Document:  81349-milr-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-milr-55342/7 government specification  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Flig:	Terminal Type:
Established  Reliability Failure Rate Level In Percent:  0.001  Body Length: 1.4 millimeters  Body Width: 3.2 millimeters  Body Height: 1.0 millimeters  Power Dissipation Rating In Watts: 0.250 free air  Style Designator: Termination pad each end  Test Data Document: 81349-mill-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-55342/7 government specification  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	Terminal type per body style
Reliability Failure Rate Level In Percent:  0.001  Body Length: 1.4 millimeters  Body Width: 3.2 millimeters  Body Height: 1.0 millimeters  Body Height: 1.0 millimeters  Power Dissipation Rating In Watts: 0.250 free air  Style Designator: Termination pad each end  Test Data Document:  81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-55342/7 government specification  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Flig:	Reliability Indicator:
Body Length:  1.4 millimeters  Body Width: 3.2 millimeters  Body Height: 1.0 millimeters  Power Dissipation Rating In Watts: 0.250 free air  Style Designator: Termination pad each end  Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-55342/7 government specification  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	Established
Body Length:  1.4 millimeters  Body Width: 3.2 millimeters  Body Height: 1.0 millimeters  Power Dissipation Rating In Watts: 0.250 free air  Style Designator: Termination pad each end  Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-55342/7 government specification  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No Fig:	Reliability Failure Rate Level In Percent:
1.4 millimeters  Body Width: 3.2 millimeters  Body Height: 1.0 millimeters  Power Dissipation Rating In Watts: 0.250 free air  Style Designator: Termination pad each end  Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-55342/7 government specification  Shelf Life: N/a  Unit Of Measure: Demilitarization: No Fig:	0.001
Body Width:  3.2 millimeters  Body Height:  1.0 millimeters  Power Dissipation Rating In Watts:  0.250 free air  Style Designator:  Termination pad each end  Test Data Document:  81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-55342/7 government specification  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Body Length:
3.2 millimeters  Body Height: 1.0 millimeters  Power Dissipation Rating In Watts: 0.250 free air  Style Designator: Termination pad each end  Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-55342/7 government specification  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	1.4 millimeters
Body Height:  1.0 millimeters  Power Dissipation Rating In Watts: 0.250 free air  Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-55342/7 government specification  Shelf Life: N/a  Unit Of Measure: Demilitarization: No Fig:	Body Width:
1.0 millimeters  Power Dissipation Rating In Watts:  0.250 free air  Style Designator:  Termination pad each end  Test Data Document:  81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-55342/7 government specification  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	3.2 millimeters
Power Dissipation Rating In Watts:  0.250 free air  Style Designator:  Termination pad each end  Test Data Document:  81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-55342/7 government specification  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Body Height:
O.250 free air  Style Designator:  Termination pad each end  Test Data Document:  81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-55342/7 government specification  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	1.0 millimeters
Style Designator:  Termination pad each end  Test Data Document:  81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-55342/7 government specification  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Power Dissipation Rating In Watts:
Termination pad each end  Test Data Document:  81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-55342/7 government specification  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	0.250 free air
Test Data Document:  81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-55342/7 government specification  Shelf Life: N/a  Unit Of Measure:   Demilitarization: No  Fiig:	Style Designator:
81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-55342/7 government specification  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	Termination pad each end
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-55342/7 government specification  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-55342/7 government specification  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Specification Data: 81349-mil-r-55342/7 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
81349-mil-r-55342/7 government specification  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Specification Data:
N/a Unit Of Measure: Demilitarization: No Fiig:	81349-mil-r-55342/7 government specification
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization:  No  Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0